

In the Claims

Please amend the claims as follows:

1 1. (Currently Amended) A method of image data processing  
2 comprising the steps of:

3 dividing an image into a plurality of two dimensional tiles,  
4 each tile <sup>comprised of</sup> having a first predetermined number of image pixels  
5 adjacently disposed in a single scan line and <sup>having</sup> a second  
6 predetermined number of adjacent scan lines;

7 storing image data in a memory having data words of a  
8 predetermined data width, each data word including a ~~plurality~~ <sup>in</sup> said  
9 first predetermined number of image pixels adjacently disposed on a  
10 single scan line, a set of a said second predetermined number of  
11 consecutive data words corresponding to a two dimensional tile of  
12 an image, whereby adjacent data words include image pixels of  
13 adjacent scan lines;

14 transferring a tile of image data from the memory to a cache;  
15 performing image operations upon said tile of image data  
16 transferred to the cache; and

17 transferring said tile of image data from the cache to the  
18 memory.

1 2. (Previously Amended) The method of claim 1, wherein:

2 said steps of transferring a tile of image data from the  
3 memory into the cache, performing image operations upon said tile  
4 of image data transferred to the cache, and transferring said tile  
5 of image data from the cache to the memory are repeated for each  
6 tile of image data.

1 3. (Previously Amended) The method of claim 1, wherein:

2 said steps of transferring a tile of image data from the  
3 memory into the cache, performing image operations upon said tile

4 of image data transferred to the cache, and transferring said tile  
5 of image data from the cache to the memory are performed by  
6 different data processors for different tiles.

1 4 (Previously Amended) The method of claim 1, wherein:  
2 said image operations includes read, modify and write of  
3 individual pixels within a data word.

1 5. (Currently Amended) An image data processing system  
2 comprising:

3 a memory storing image data having data words of a  
4 predetermined data width, each data word including a plurality  
5 first predetermined number of image pixels adjacently disposed on a  
6 single scan line, a set of a second predetermined number of  
7 consecutive data words corresponding to a two dimensional tile of  
8 said first predetermined number of image pixels and said second  
9 predetermined number of scan lines of an image, whereby adjacent  
10 data words include image pixels of adjacent scan lines;

11 a tile cache capable of storing a tile of image data from said  
12 memory;

13 a data processing apparatus connected to said memory and said  
14 tile cache, said data processing apparatus programmed to

15 transfer a tile of image data from said memory into said  
16 tile cache,

17 perform an image operation upon said tile of image data  
18 transferred to said tile cache, and

19 transfer that tile of image data from said tile cache to  
20 said memory.

1 6. (Previously Amended) The image data processing system of  
2 claim 5, wherein:

3        said data processing apparatus is further programmed to  
4 sequentially operate upon different tiles of image data.

1        7. (Previously Amended) The image data processing system of  
2 claim 5, further comprising:

3        a second data processing apparatus connected to said memory  
4 and said tile cache, said second data processing apparatus  
5 programmed to

6        transfer a tile of image data from said memory to said  
7 tile cache,

8        perform an image operation upon said tile of image data  
9 transferred to said tile cache, and

10       transfer that tile of image data from said tile cache to  
11 said memory; and

12       wherein said data processing apparatus and said second data  
13 processing apparatus are programmed to operate upon different tiles  
14 of image data simultaneously.

1        8. (New) The method of claim 1, wherein:

2        <sup>the</sup> said step of transferring a tile of image data from the memory  
3 to a cache includes making said second predetermined number of page  
4 mode DRAM accesses; and

5        said step of transferring said tile of image data from the  
6 cache to the memory includes making said second predetermined  
7 number of page mode DRAM accesses.

1        9. (New) The image data processing system of claim 5,  
2 wherein:

3        said memory includes a DRAM supporting page mode accesses; and  
4        said data processing apparatus is further programmed to

C/

5           transfer a tile of image data from said memory into said  
6   tile cache via said second predetermined number of page mode  
7   DRAM accesses, and  
8           transfer that tile of image data from said tile cache to  
9   said memory via said second predetermined number of page mode  
10   DRAM accesses.

---